

Product data sheet

TS 1500 with hold-open arm



Overhead door closer with link arm for single leaf doors with a leaf width up to 1100 mm

AREAS OF APPLICATION

- Right and left single-action doors
- Holds doors without smoke and fire protection requirements open
- Single-action doors up to 1100 mm leaf width
- Door leaf installation hinge side and transom installation opposite hinge side
- Door leaf installation opposite hinge side in parallel arm installation possible

TS 1500 with hold-open arm



PRODUCT FEATURES

- Variable closing force of EN3 or EN4 by reversing the bearing block
- Can be used for right and left hand doors without conversion
- Mechanical hold-open unit through hold-open linkage with hold-open area 70°-150°
- Hydraulic latching action which accelerates the door shortly before it is closed
- Closing speed can be individually adjusted

TECHNICAL DATA

Productname	TS 1500 with hold-open arm
Closing force in accordance with EN 1154	EN 3/4
Leaf width (max.)	1100 mm
Type of installation	Door leaf installation hinge side, Door leaf installation opposite hinge side, Transom installation opposite hinge side
Opening angle (max.)	180 °
Closing force adjustable	Yes, via installation
Adjustable closing speed	Yes
Latching action adjustable	Yes, via link arm
Hold-open range	70 ° - 150 °
Smoke switch integrated	No

ACCESSORIES

LINK ARM TS 4000 / 2000

With mechanical hold-open device



Designation	Description	Ident-No.	Colour	Hold-open point min.	Hold-open point max.
Link arm TS 4000/2000 / F	With mechanical hold-open device	102454	silver-coloured	70 °	150 °
Link arm TS 4000/2000 / F	With mechanical hold-open device	102456	white RAL 9016	70 °	150 °
Link arm TS 4000/2000 / F	With mechanical hold-open device	102457	according to RAL	70 °	150 °

TS 1500 with hold-open arm



LINK ARM TS 4000 / 2000

with mechanical hold-open device which can be switched on and off



Designation	Description	Ident-No.	Colour	Hold-open point min.	Hold-open point max.
Link arm TS 4000/2000 / F	with mechanical hold-open device which can be switched on and off	102445	silver-coloured	70 °	150 °
Link arm TS 4000/2000 / F	with mechanical hold-open device which can be switched on and off	102448	according to RAL	70 °	150 °
Link arm TS 4000/2000 / F	with mechanical hold-open device which can be switched on and off	102447	white RAL 9016	70 °	150 °