

Product data sheet

Powerturn / Powerturn F roller guide rail



For transom installation on the hinge side or opposite hinge side with roller guide rail

AREAS OF APPLICATION

- Reveal depth of 0 - 200 mm
- Fire protection doors permitted until reveal depth of 100 mm



PRODUCT FEATURES

- Opening angle depends on reveal depth
- Compatible with integrated opening restrictor
- Special profile to prevent rollers jumping out

TECHNICAL DATA

Productname	Powerturn / Powerturn F roller guide rail
DIN left	Yes
DIN right	Yes

VARIANTS / ORDER INFO

Designation	Description	Ident-No.	Colour	Type of installation
Roller guide rail Powerturn (F)	For transom installation opposite hinge side, length 691 mm, lever length 450 mm	153813	according to RAL	Transom installation opposite hinge side
Roller guide rail Powerturn (F)	For transom installation opposite hinge side, length 691 mm, lever length 450 mm	153812	EV1	Transom installation opposite hinge side
Roller guide rail Powerturn (F)	For transom installation hinge side, length 691 mm, lever length 330 mm	153790	according to RAL	Transom installation hinge side
Roller guide rail Powerturn (F)	For transom installation hinge side, length 691 mm, lever length 330 mm	153787	EV1	Transom installation hinge side