

# Product data sheet GEZE ActiveStop surface mounted configured \*



Door damping on both sides for interior swing doors, configured for timber or glass doors

#### **AREAS OF APPLICATION**

- → Right and left single-action doors for interior use
- → Room doors with high access convenience
- → Single-action doors up to 1100 mm leaf width
- → Surface-mounted installation, for retrofitting on existing doors
- → Barrier-free access in accordance with DIN 18040-2

### GEZE ActiveStop surface-mounted configured



#### **PRODUCT FEATURES**

- → Door opening angle with variable adjustment from 80°-140°
- → Can be used for right and left hand doors without conversion
- → Soft opening and closing of doors up to max. 45 kg leaf weight
- → Gentle stopping, quiet closing and comfortable keeping open of doors
- → Practically eliminates slamming doors, trapped fingers, and damage to walls and furniture
- $\rightarrow$  Secure holding of the door when open, meaning no door is stopper necessary
- ightarrow Opening and latching speed when installed can be set via a valve
- → Integrated safety valve offers overload protection

#### TECHNICAL DATA

Productname	GEZE ActiveStop surface-mounted configured * 34 mm		
Depth			
Height	68 mm		
Leaf weight (max.)	45 kg		
Leaf width (max.)	1100 mm		
Category of door	flush-mounted, rebated		
Identical design for DIN left and DIN right	Yes		
Installation type	surface-mounted		
Adjustable draw-in damper	Yes, via valve		
Draw-in damper in direction of closing movement from	25 °		
Free swing area	25 ° - 60 °		
Draw-in damper in direction of opening movement from	60°		
Adjustable door opening angle	Yes, stepless		
Hold-open position adjustable	80 ° - 140 °		
Safety valve againts overload	Yes		

#### **VARIANTS / ORDER INFO**

		ldent-			DIN
Designation	Description	No.	Colour	Dimensions	direction
GEZE ActiveStop surface- mounted configured *	Door damping on both sides for interior swing doors, configured for timber or glass doors	184107	according to RAL	370 x 68 x 34 mm	left / right

GEZE GmbH | Reinhold-Vöster-Straße 21-29 | D-71229 Leonberg | TEL +49 7152 203-0 | WEB www.geze.de | Mail info.de@geze.com

Product data sheet I Page 3 of 3

## GEZE ActiveStop surface-mounted configured \*



#### ACCESSORIES

#### **FASTENING SET FOR SPECIAL GLASS \***

For fastening the GEZE ActiveStop surface-mounted on satin-finish glass



<sup>\*</sup> The products designated above may vary in form, type, characteristics, function, or availability depending on the country. Please get in touch with your GEZE contact person if you have any questions.

**GEZE GmbH** Reinhold-Vöster-Straße 21–29 D-71229 Leonberg TEL +49 7152 203-0 WEB www.geze.de Mail info.de@geze.com 2024-03-30T04:00:10Z